

QUATRAC PRO+

SIZE RANGE

Size	R	Inch	LI	SI	XL	FSL	Size	R	Inch	LI	SI	XL	FSL
285 35	R	22	106	Y	Yes	Yes	225 40	R	18	92	V	Yes	Yes
285 40	R	22	110	Y	Yes	Yes	215 40	R	18	89	Y	Yes	Yes
275 40	R	22	108	Y	Yes	Yes	245 45	R	18	100	Y	Yes	Yes
295 35	R	21	107	Y	Yes	Yes	235 45	R	18	98	Y	Yes	Yes
245 35	R	21	96	Y	Yes	Yes	225 45	R	18	95	Y	Yes	Yes
285 40	R	21	109	Y	Yes	Yes	215 45	R	18	93	Y	Yes	Yes
275 40	R	21	107	Y	Yes	Yes	235 50	R	18	101	V	Yes	Yes
265 40	R	21	105	Y	Yes	Yes	225 50	R	18	99	W	Yes	Yes
285 45	R	21	113	Y	Yes	Yes	215 50	R	18	92	W	No	Yes
275 45	R	21	110	Y	Yes	Yes	255 55	R	18	109	W	Yes	Yes
275 30	R	20	97	Y	Yes	Yes	235 55	R	18	104	V	Yes	Yes
315 35	R	20	110	Y	Yes	Yes	225 55	R	18	102	V	Yes	Yes
255 35	R	20	97	Y	Yes	Yes	215 55	R	18	99	V	Yes	Yes
245 35	R	20	95	Y	Yes	Yes	255 60	R	18	112	V	Yes	Yes
275 40	R	20	106	Y	Yes	Yes	235 60	R	18	107	W	Yes	Yes
255 40	R	20	101	Y	Yes	Yes	225 60	R	18	104	W	Yes	Yes
245 40	R	20	99	Y	Yes	Yes	235 65	R	18	110	V	Yes	Yes
285 45	R	20	112	Y	Yes	Yes	215 40	R	17	87	Y	Yes	Yes
275 45	R	20	110	Y	Yes	Yes	205 40	R	17	84	W	Yes	Yes
265 45	R	20	108	Y	Yes	Yes	245 45	R	17	99	Y	Yes	Yes
255 45	R	20	105	W	Yes	Yes	235 45	R	17	97	Y	Yes	Yes
245 45	R	20	103	W	Yes	Yes	225 45	R	17	94	Y	Yes	Yes
235 45	R	20	100	W	Yes	Yes	215 45	R	17	91	Y	Yes	Yes
265 50	R	20	111	Y	Yes	Yes	205 45	R	17	88	Y	Yes	Yes
255 50	R	20	109	Y	Yes	Yes	205 45	R	17	88	V	Yes	Yes
255 55	R	20	110	Y	Yes	Yes	225 50	R	17	98	Y	Yes	Yes
195 55	R	20	95	H	Yes	Yes	215 50	R	17	95	W	Yes	Yes
275 35	R	19	100	Y	Yes	Yes	205 50	R	17	93	Y	Yes	Yes
255 35	R	19	96	Y	Yes	Yes	205 50	R	17	93	V	Yes	Yes
235 35	R	19	91	Y	Yes	Yes	275 55	R	17	109	V	No	Yes
255 40	R	19	100	Y	Yes	Yes	235 55	R	17	103	Y	Yes	Yes
245 40	R	19	98	Y	Yes	Yes	235 55	R	17	103	V	Yes	Yes
235 40	R	19	96	Y	Yes	Yes	225 55	R	17	101	W	Yes	Yes
255 45	R	19	104	Y	Yes	Yes	215 55	R	17	98	W	Yes	Yes
245 45	R	19	102	Y	Yes	Yes	205 55	R	17	95	V	Yes	Yes
235 45	R	19	99	Y	Yes	Yes	255 60	R	17	106	V	No	Yes
225 45	R	19	96	W	Yes	Yes	235 60	R	17	106	V	Yes	Yes
265 50	R	19	110	W	Yes	Yes	225 60	R	17	103	V	Yes	Yes
255 50	R	19	107	Y	Yes	Yes	215 60	R	17	100	V	Yes	Yes
235 50	R	19	103	W	Yes	Yes	215 60	R	17	96	H	No	Yes
255 55	R	19	111	W	Yes	Yes	265 65	R	17	116	H	Yes	Yes
235 55	R	19	105	W	Yes	Yes	245 65	R	17	111	V	Yes	Yes
225 55	R	19	103	W	Yes	Yes	235 65	R	17	108	W	Yes	Yes
245 40	R	18	97	Y	Yes	Yes	225 65	R	17	106	V	Yes	Yes
235 40	R	18	95	Y	Yes	Yes	215 65	R	17	103	V	Yes	Yes
225 40	R	18	92	Y	Yes	Yes							



QUATRAC PRO+




VREDESTEIN
TYRES

PRODUCT HIGHLIGHTS

VREDESTEIN
TYRES

United Kingdom: Apollo Tyres (UK) Ltd., Tel. 0330 333 1294, E-mail: customer.uk@apollotyres.com
Export: Apollo Tyres (Europe) B.V., Tel. +31-53-4 888 400, E-mail: export@apollotyres.com

ALL-SEASON WITH A BIG PLUS



QUATRAC PRO+

BENEFITS

- Best-in-class on wet roads
- Upgraded snow performance
- Improved fuel efficiency

FEATURES

- Strong water evacuation against aquaplaning
- 5% better on snow grip and acceleration*
- 5% lower rolling resistance

* Data based on internal testing against predecessor Quatrac Pro in development size 245/45 R 18 100Y XL

DNA OF THE QUATRAC PRO+

Build on 30 years of All-Season experience

Widest range of All-Season tyres in the market

Specially designed for high performance Cars & SUVs

ADVANCED TECHNOLOGY

- Wider longitudinal grooves combined with diverging grooves in the shoulder optimise water evacuation from the tread pattern.
- Sophisticated compound with high silica and resin content to give excellent traction on wet surfaces.
- Distinctive winter and summer side to ensure high performance in all weather conditions.

- A lot easier to control - with better steering response, more stability and better recovery - on snow and slush.
- Low temperature flexibility coming from a tailor-made blend of new generation polymer and resin.
- Highly equal pressure distribution means sipes in the centre area are very effective on snow.

- About 5% reduction in rolling resistance due to optimized polymer-filler interaction in tread rubber.
- Compound stiffness is synergetic with pattern thickness - better stability of tyre over all temperature range.